



DiNiv 100

Nivela Digitala Automata cu citire pe Stadie cu Cod de Bare



Technical data		Date Tehnice
Mean error for 1 km double levelling		Eroarea medie la 1 Km dubla nivelare
Optical reading	± 1,5 mm	Citire optica
Electronic reading	± 1,5 mm	Citire electronica
Maximum measuring distance	100 m	Distanta maxima masurata electronic
Minimum measuring distance	2,5 m	Distanta minima masurata
Time of single measurement	3 sec.	Timpul pentru o singura masurare
Minimum reading of altitude	0,2 mm	Citirea minima a inaltimei
Minimum reading of distance	0,01 m	Citirea minima a distantei
Telescope		Telescop
Magnification	28x	Magnificare
Aperture	40 mm	Deschidere
Shortest distance	0,5 m	Cea mai mica distanta
Circular bubble	8' / 2 mm	Bula circulara
Range of compensator	± 15'	Interval compensator
Levelling accuracy	± 0,5"	Precizie nivelare compensator
Measuring programs		Programe masurare
Height differences		Diferente de inaltime
Distance		Distanta
Set altitude		Setare altitudine
Internal memory / measurements	2000	Memorie interna / Masurari
Data transfer to PC via RS-232/USB		Transfer Date la PC prin RS-232/USB
Dust/Waterprotection	IP54	Protectie Praf/Apa ploaie
Power supply rechargeable	6V/1,3Ah	Sursa alimentare reincarcabila
Continuous working time	10 h	Timp masurare continua
Weight	2,5 kg	Greutate
Supplied with:		Suplimentar cu:
rechargeable battery with charger,		baterii incarcabile, cu incarcator
container, transfer cable, software,		cutie transport, cablu transfer, software
battery case for alkaline batteries,		capac pentru baterii alcaline,
lens hood		Parasolar
Article No.: DiNiv 100	200750	Articol nr: DiNiv 100
Article No.: Barcode Staff 5 m	200755	Articol nr.: Cod de bare 5 m

